

DESIGNED TO **SIMPLIFY** LIFE
ENGINEERED TO **MAGNIFY** RESULTS



AGROLUX 4.80

For more information visit deutz-fahr.co.za or contact 0861 128 128

DEUTZ-FAHR is a trademark of  SDF



TECHNICAL DATA		AGROLUX	
		4.80	
		2WD	4WD
ENGINE			
Manufacturer		SDF 1000.3 WT	
Emissions		Tier 2	
Cylinders/Capacity	No./cm ³	4/4 000	
Naturally aspirated		•	
Max. Power	kW/hp	75/54.4	
Max. Engine speed (rated)	rpm	2 350	
Max. Torque	Nm	270	
Air cleaner with dust ejector		•	
Cooling liquid		•	
Under-hood silencer		vertical exhaust	
Fuel tank capacity	litres	70	
Biodiesel fuel	%	B100	
MECHANICAL GEARBOX			
Synchronised		•	
Electro-hydraulic engagement differential lock		-	
Number of speeds	n°	12FW + 3Rev	
Number of speeds with creeper		-	
Minimum speed/Minimum speed with creeper	km/h	-	
Maximum speed	km/h	30	
Hydrostatically operate self-adjusting dry clutch, single		•	
REAR P.T.O.			
Electro-hydraulic clutch with multiple discs		-	
PTO 540/540ECO		•	
FRONT AND REAR AXLE			
Mechanically operated		•	
Steering angle	degrees	55°	
BRAKES			
Oil immersed disc brakes and all 4WD braking		•	
Parking brake		•	
STEERING			
Hydrostatically steering		•	
HITCH			
Category		II	
Mechanical rear hitch		•	
Maximum lift capacity	kg	3 000	
HYDRAULIC SYSTEM			
Pump output (std)	litres/min	42	
Auxiliary distributors	n°	1/2/4/6	
DRIVING POSITION			
Driver seat with mechanical suspension		•	
Analogue instrumentation		•	
DIMENSIONS AND WEIGHTS			
Standard rear tyres		16.9 - 30	16.9R30
Standard front tyres		7.50 - 16	11.2R24
Length	mm	3 445	
Width (min.-max.)	mm	1 985 -2 285	
Wheelbase	mm	2 105	2 160
Front track (min.-max.)	mm	1 780	1 750
Rear track (min.-max.)	mm	1 902	
Ground clearance	mm	400	
Weight	kg	2 560	2 820

STD • | OPT ° | - Not available | *if this limit is permitted

Technical data and pictures are guidelines only. Whilst making every effort to meet your requirements, DEUTZ-FAHR may make changes at any time and is not required to give notice thereof.